

Ground Mount Enclosures

for Power Supply/UPS with Top Terminal Batteries



Ground mount outdoor rated enclosures for cable telecommunications and broadband applications. Accommodates one power supply/UPS with and 0 to 8 Group 27 or 31 sized top terminal batteries. Includes: ground skirt/pedestal, cable network power interface with bypass switch, enclosure status LED, all cables to support/connect specified number of batteries. Optional: exhaust fan, utility meter base, breaker box, and AC or DC generator interface.

FEATURES

- ◆ Universal NEMA 3R enclosure – accommodates many brands of power supplies
- ◆ Available in 0, 1, 2, 3, 4, 6 and 8 battery count versions
- ◆ Standard 120VAC or 240VAC duplex outlet (dependent on model)
- ◆ Designed for use with top-terminal batteries
- ◆ Built-in high current alt/bypass switch with cable network power interface
- ◆ Includes all power battery cables
- ◆ Secure rear cable raceway
- ◆ Status LED indicator
- ◆ Battery slide tray with locking latches
- ◆ Lightweight corrosion resistant aluminum enclosure
- ◆ UV protected powder-coat finish
- ◆ Optional:
 - Meter-base and high-mag breaker box
 - Integrated automatic AC generator or DC generator interface
 - Exhaust fan



BASIC CHARACTERISTICS

MYERS EPS MODEL #							
	CSEGI Series*	CSEG2 Series	CTEG0 Series*	CTEG3 Series	CTEG4 Series	CTEG6 Series	CTEG8 Series
DIMENSIONS H x W x D INCHES (CM)	23.6 x 24.5 x 15.5 (60 x 62.2 x 40)	35.5 x 18.5 x 15.5 (90 x 47 x 40)	35.5 x 24.5 x 15.5 (90 x 62.2 x 40)	35.5 x 25 x 15.5 (90 x 63 x 40)	35.5 x 28.8 x 17.5 (90 x 73.2 x 44.5)	46.5 x 24.5 x 15.5 (99 x 61.6 x 39.4)	46.5 x 28.8 x 17.5 (118 x 73 x 44.5)
WEIGHT LBS (KG)	31 (14)	42 (19)	46 (20.8)	54 (25)	70 (32)	78 (35)	85 (39)
USE WITH PRE-CAST PAD	CTEG-PAD-36-MTL				CTEG-PAD-48-MTL	CTEG-PAD-36-MTL	CTEG-PAD-48-MTL
USED WITH:	TSP, SSP-12	SSP-12, SSP-24	TSP	TSP, SSP-12, SSP-24, SSP-36		TSP, SSP	
APPLICATION	TSP – TM only or TM/EM with separate battery location SSP-12 with 1 battery	SSP-12 with 1 or 2 batteries SSP-12 with 1 two battery string	TSP with no batteries TSP with 1 three battery string, batteries slid out for service	TSP with 1 three battery string Two SSP-12's each with 1 battery (one set per shelf) SSP-24 with 1 two battery string SSP-36 with 1 three battery string	TSP with 1 four battery string Two SSP-12's each with 2 batteries (one set per shelf) SSP-24 with up to 2 two battery strings SSP-36 with 1 three battery string	TSP with 2 three battery strings SSP – too many to list	TSP with 2 four battery strings SSP – too many to list

* No battery drawer in the CSEGI and CTEG0

OPTIONS

OPTION DESCRIPTION	ORDERING INFORMATION
Thermostatically Controlled Enclosure Fan Kit; Provides forced air cooling	To order preinstalled, add suffix " " to model number. ex. CTEG3-120F Customer installed fan kit is model number: CTE-FAN-KIT
External Meter-base and Breaker Box, Single Phase, 20Amp, High-Mag	Preinstalled, add suffix "M " to model number. ex. CTEG3-120MB
AC Generator Interface; Auto switches AC input to Generator when Generator is on.	Preinstalled, add suffix "GI" o model number: ex. CTEG6-120GI
DC Generator Interface; Plug DC generator into lockable external box	To order preinstalled, add suffix "DI" o model number: ex. CTEG6-120DI For customer installation, order box CTE-GENCONN and cable CTSPBCK-70
Replacement Battery Cables	Order cable kit: CTSPBCKx-B (x = number of batteries in enclosure, ex. CTSPBCK3-B is for the three battery enclosure CTEG3-120)
Replacement Status LED	Order: For red LED's, CT-RED-LED, green LED's, CT-GREEN-LED Myers EPS supplies use a 2Volt LED. (Other manufacturers may use a 12Volt LED.)
Add-on Security Bar	Customer installed only. Order kit: CTEP-SEC-BAR3 for 1, 3, 6 battery enclosures, CTEP-SEC-BAR4 for 4, 8 battery enclosures (also designed to fit on ot er manufactures enclosures with similar battery counts) Locks are also available
Output Conversion Cable	Order conversion cable CT-0W5514A to use other brand equipment in a Myers EPS enclosure
AC Outlet Options for installations outside the US	All international AC outlet styles can be accommodated. Please consult your sales representative for more information.