

## FRP Series Non-Standby Power Supply Output 60V/75V/87V



The FRP series power supplies provide cost-effective non-standby 60/75/87V at 6, 15 or 18Amp for indoor or outdoor powering. Complete with outdoor enclosure and mounting bracket, it is ready for pole or wall mounting. Ideal for use where standby power is not required.

## **FEATURES**

- Complete cost-effective cable power supply
- Outdoor enclosure, ready for pole or wall mounting
- Mounting bracket included
- 120VAC 60Hz input
- Vser selectable 60/75/87 VAC output
- Security lock

- Includes pole/wall mount bracket
- LED output indicator
- Lightweight corrosion resistant aluminum enclosure
- VV protected powder-coat finish



## **SPECIFICATIONS**

| MYERS EPS MODEL NUMBER                 |  |   |   |
|--|--|---|---|
|  | CTFRP9006  | CTFRP9015   | CTFRP9018   |
| DESCRIPTION                            | Non-Standby Cable Power<br>Supply, 120VAC 60Hz<br>60/75/87V<br>(6 Amp @ 87VAC) | Non-Standby Cable Power<br>Supply, 120VAC 60Hz<br>60/75/87V<br>(15 Amp @ 87VAC) | Non-Standby Cable Power<br>Supply, 120VAC 60Hz<br>60/75/87V<br>(18 Amp @ 87VAC) |
| DIMENSIONS<br>H x W x D<br>inches (cm) | 11.5 x 9.25 x 8.25<br>(29.2 x 23.5 x 21)                                       |   |   |
| WEIGHT<br>lbs (kg)                     | 38 (17.6)  | 56 (25.5)   | 61 (27.7)   |
| HOUSING MATERIAL                       | Aluminum   |   |   |
| INPUT VOLTAGE                          | 120 VAC ± 15%  |   |   |
| INPUT FREQUENCY                        | 60 ± 1Hz   |   |   |
| OUTPUT VOLTAGE                         | 60VAC, 75VAC or 87VAC Field Selectable, ± 3%                                   |   |   |
| OUTPUT POWER<br>(CURRENT)              | 540VA<br>(6Amp @ 87V)  | 1350VA<br>(15Amp @ 87V)   | 1620VA<br>(18Amp @ 87V)   |
| EFFICIENCY                             | 87% – 94% dependent on load  |   |   |

